



CYBERMED C22 22" Medical Grade All-in-One PC



Display	<ul style="list-style-type: none"> • 22" medical grade 16:9 LED (1920x1080) 	Webcam	<ul style="list-style-type: none"> • 3 Megapixel Camera (Optional)
CPU Support	<ul style="list-style-type: none"> • 4th Generation Intel Core i3, i5 & i7 processors 	Wall Mount	<ul style="list-style-type: none"> • Supports 75mm & 100mm VESA mounting holes
I/O Ports	<ul style="list-style-type: none"> • 2x USB 3.0 ports, 4x USB 2.0 ports • 1x RS232, option to expand to 3 COM ports • Display port v1.2 max res. 3840x2160 (60Hz, 24bpp) • HDMI max res. 4K (24Hz, 24bpp); 1080p (60Hz, 36bpp) • HDMI Input (Monitor Mode) • FireWire 800 Mini • Mic, Line-In, Line-Out 	Bios	<ul style="list-style-type: none"> • AMI Flash BIOS supports ACPI, API, DMI, Plug & Play, and security password. Supports booting from HDD, PXE, LAN, CD-ROM, and ANY USB device. Has BIOS System POST and BIOS setup password protection
Chipset	<ul style="list-style-type: none"> • Intel H81 	Expansion Slots	<ul style="list-style-type: none"> • Two Mini PCI-e (2x Full-Size)
Memory	<ul style="list-style-type: none"> • 2x DDR3/1600MHz 204-pin SO-DIMM sockets, populated up to 16GB Max 	HDD Support	<ul style="list-style-type: none"> • Integrated Serial ATA controller facilitates high-speed transfers up to 6Gbps
Operating System	<ul style="list-style-type: none"> • Window 10, Windows 8, Windows 7, Linux 	Weight	<ul style="list-style-type: none"> • 14.40 lbs
Video & Graphics	<ul style="list-style-type: none"> • Intel HD Graphics, Optional NVIDIA GeForce GT720M GPU with 2GB DDR 	Dimensions	<ul style="list-style-type: none"> • 21.81" x 14.61" x 2.13" (L, W, D)
Networking	<ul style="list-style-type: none"> • 1x Gigabit (Gbe) Intel i217V Clarkville • 1x Gigabit (Gbe) Fast Ethernet Realtek RTL 8111G 	Colors	<ul style="list-style-type: none"> • White with Antimicrobial Germ Protection
Audio	<ul style="list-style-type: none"> • Realtek ALC892 High Definition Audio, Dolby Digital 5.1 surround sound, 10 channels of enhanced sound quality, multiple audio streams and jack re-tasking 	Power Supply	<ul style="list-style-type: none"> • Medical Grade 120W 100 ~ 240V AC, 50-60Hz. Supports Output range: DC 18V-19V, 7.5A
Environment	<ul style="list-style-type: none"> • Ambient Temperature: 0°C ~ 40°C (operating) 	Relative Humidity	<ul style="list-style-type: none"> • 10% ~ 90% (non-condensing)
Touch Screen	<ul style="list-style-type: none"> • PCAP Multi Touch with Antiglare Technology 	Certifications	<ul style="list-style-type: none"> • EN60601-1 medically certified, UL60950 electrical safety, FCC class B, CE, Energy Star 6.1, RoHS 2 WEEE
Wireless	<ul style="list-style-type: none"> • 802.11 b/g/n with Bluetooth 4.0 	Swivel Base	<ul style="list-style-type: none"> • Optional desktop stand with Antimicrobial Germ protection with rotation function Left/Right plus tilt function Up/Down
Optional	<ul style="list-style-type: none"> • Smart Card (CAC Reader) • RFID Reader 	Waterproof	<ul style="list-style-type: none"> • IP65 Front Bezel and IPX1 Back Cover