
















	DICOM				CLINICAL REVIEW				DIAGNOSTIC			MULTI-MODALITY/ MAMMOGRAPHY			TOUCH PANEL
	EV2451 2MP COLOUR	EV2456 2MP COLOUR	EV2750 4MP COLOUR	EV2785 8.3MP COLOUR	MX194 1MP COLOUR	MX215 2MP COLOUR	MX242X 2.3MP COLOUR	MX315W 8.8MP COLOUR	RX250 2MP COLOUR	RX350 3MP COLOUR	RX660 6MP COLOUR	RX850 8.8MP COLOUR	RX560 5MP COLOUR	GX560 5MP MONOCHROME	MS236WT 2MP COLOUR
															
SIZE	60 cm / 23.8"	61 cm / 24.1"	27 cm /68.5"	27 cm /68.5"	48 cm / 19.0"	54 cm / 21.3"	61 cm / 24.1"	79 cm /31.1"	54 cm / 21.3"	54.1 cm / 21.3"	76 cm / 30.0"	79 cm / 31.1"	54.1 cm / 21.3"	54.1 cm / 21.3"	58 cm / 23.0"
RESOLUTION	1920 x 1080	1920 x 1200	2560 x 1440	3840 x 2160	1200 x 1600	1200 x 1600	1920 x 1200	4096 x 2160	1200 x 1600	1536 x 2048	3280 x 2048	4096 x 2160	2048 x 2560	2048 x 2560	1920 x 1080
MAXIMUM BRIGHTNESS	250 cd/m ²	300 cd/m ²	350 cd/m ²	350 cd/m ²	350 cd/m ²	420cd/m ²	420cd/m ²	450 cd/m ²	800 cd/m ²	1,000 cd/m ²	1,000 cd/m ²	850 cd/m ²	1100 cd/m ²	2,500 cd/m ²	260 cd/m ²
CALIBRATED BRIGHTNESS	not specified	not specified	not specified	not specified	180 cd/m ²	180 cd/m ²	180 cd/m ²	270 cd/m ²	400 cd/m ²	500 cd/m ²	500 cd/m ²	500 cd/m ²	500 cd/m ²	600 cd/m ²	not specified
CONTRAST RATIO	1000:1	1000:1	1000:1	1300:1	2000:1	1500:1	1000:1	1300:1	1400:1	1500:1	1500:1	1450:1	1500:1	1700:1	1000:1
SIMULTANIOUS DISPLAY TONES	10 bit	10 bit	10 bit	10 bit	8 bit	10 bit	10 bit	10 bit	10 bit	10 bit	10 bit	10 bit	10 bit	10 bit	8 bit
SIGNAL INPUTS	DVI-D x 1, DP x 1, HDMI x 1 D- Sub mini 15 pin x 1	DVI-D x 1, DP x 1, HDMI x 1 D- Sub mini 15 pin x 1	DP x 1, DVI-D 24 pin x 1, HDMI x 1 (All with HDCP)	USB Type-C x 1, DP 1.2 x 1, HDMI x 2 (All with HDCP)	DVI-D x 1, DP x 1, D-Sub mini 15 pin x 1	DVI-I x 1, DisplayPort x 1	DVI-I x 1, DisplayPort x 1	DVI-D (dual link) x 1, DisplayPort X 2	DVI-D x 1, DisplayPort x 1	DVI-D (dual link) x 1, DisplayPort x 1	DVI-D (dual link) x 1, DisplayPort x 2	DVI-D (dual link) x 2, DisplayPort x 2 (two inputs required)	DVI-D (dual link) x 1, DisplayPort x 1	DVI-D (dual link) x 1, DisplayPort x 1	DVI-D x 1, DP x 1, D- Sub mini 15 pin x 1
MEETS RANZCR STANDARDS FOR DIAGNOSTIC REPORTING										✓	✓	✓	✓	✓	
FDA (510K) MAMMOGRAPHY & TOMOSYNTHESIS												✓	✓	✓	
HYBRID GAMMA Distinguishes between monochrome & color images, displays each in optimum brightness & greyscale tones.									✓	✓	✓	✓	✓	✓	
INTEGRATED FRONT SENSOR						✓		✓	✓	✓	✓	✓	✓	✓	
PRESENCE SENSOR Power Savings. Auto power-off when not in use	✓	✓	✓	✓		✓		✓	✓	✓	✓	✓	✓	✓	
AUTOMATED QC					✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
DIGITAL UNIFORMITY EQUALIZER Optimum brightness uniformity across the screen					✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
WARRANTY	5 Years	5 Years	5 Years	5 Years	5 Years/ 15,000h at calibrated brightness	5 Years/ 15,000h at calibrated brightness	5 Years/ 15,000h at calibrated brightness	5 Years/ 10,000h at calibrated brightness	5 Years/ 20,000h at calibrated brightness (or 5 Years/ 30,000h at 400cd/m2)	Years/ 20,000h at calibrated brightness (or 5 Years/ 30,000h at 400cd/m2)	5 Years/ 20,000h at calibrated brightness (or 5 Years/ 30,000h at 400cd/m2)	5 Years/ 20,000h at calibrated brightness (or 5 Years/ 30,000h at 400cd/m2)	5 Years/ 20,000h at calibrated brightness	5 Years/ 20,000h at calibrated brightness	3 Years