



## CLEANWIPE™ WATERPROOF MEDICAL KEYBOARDS

Model: SSKSV099, SSWKSV099

State-of-the-art CleanWipe Waterproof Keyboards from Seal Shield.™ Keyboard with a compact footprint perfect for any workspace. Washable, waterproof & dishwasher-safe keyboard is IP68 certified (highest rating), compatible with medical-grade cleaners & disinfectants. UV-resistant coating on key labels enhance durability and product longevity throughout regular and vigorous cleaning. CleanWipe latex-free silicone cover is included.

## **FEATURES:**



100% Waterproof & Dishwasher-Safe



IP68 Certified (highest waterproof rating)



Contains an antimicrobial agent to prevent microorganisms from degrading the product



USB Quick Connect Cable with Seal Cap™



UV-Resistant Coating on Key Labels



Compatible with Hospital Cleaners & Disinfectants



Compact footprint perfect for tight applications including mobile carts and exam rooms



SSWKSV099



SSKSV099

#### MEDICAL-GRADE CLEANING CAPABILITIES

- · Dishwasher-Safe (Hot & Cold settings)
- · Bleach compatible. Clorox® approved. (including Clorox HealthCare Products)
- · Disinfectants & Sporicides (including Lysol® products EPA-certified to kill COVID-19)

· Alcohol and H. Peroxide

HEALTHCARE

· Solvents, Corrosives and Acids





### PRODUCT DATASHEET



# CLEANWIPE™ WATERPROOF MEDICAL KEYBOARDS

Model: SSKSV099, SSWKSV099

### **TECHNICAL DATA:**

Compatibility:	Window®s,Mac® (USB Models)
Construction:	ABS Plastic (Chiclet Style with Silicone Cover)
Net Dimensions L x W x H:	13.52 x 4.45 x 1.0in (34.35 x 11.3 x 2.5cm)
Gross Dimensions:	14.05 x 4.53 x 1.3in (35.7 x 11.5 x 3.30cm)
Key Layout:	99 US
Net Weight:	.584lb (.265kg)
Gross Weight:	.705lb (.320kg)
Connection Type:	USB with 6ft (1.83m) Cable
Key Switch Force:	60 ± 15 gf
Key Switch Life Cycle:	8,000,000 cycles +
Key Switch Type:	Chiclet Style with Scissor Mechanism
Keycaps Imaging Type:	Screen Printed with UV Protective Coating
Power Consumption:	1.5mW
Total Key Travel:	.08 in (2mm)
Operating Voltage:	+ 5VDC ± 5%
Storage Temperature:	-5° to 55° C
EMI - RFI:	Conforms to FCC Rules for Class B Computing Device
Waterproof/Dustproof Ratings:	IP68, NEMA 4X
Approvals/Certifications:	FCC, CE, RoHS WEEE, WHQL ICES-003, RSS-210



Copyright© 2020, Seal Shield, LLC. All rights reserved. All other trademarks and trade names are those of their respective owners Limited 2-Year Warranty